

BOGE Typ	Höchstdruck		Behälter- inhalt Liter	Effektive Liefer- menge* 50 Hz		Effektive Liefer- menge* 60 Hz		Motorleistung		Behälter- option Liter	Maße B x T x H			Gewicht kg
	bar	psig		m ³ /min	cfm	m ³ /min	cfm	kW	PS		mm	mm	mm	
CL 3-	10	150	90	0,240	9	–	–	2,2	3,0	270	1130 x 490 x 920	155		
CL 4-	10	150	90	0,340	12	0,31	11	3,0	4,0	270	1130 x 490 x 920	160		
CL 4-	13	190	90	0,234	8	–	–	3,0	4,0	270	1130 x 490 x 920	165		
CL 5-	10	150	90	0,545	19	0,40	14	4,0	5,5	270	1130 x 490 x 920	175		
CL 7-	10	150	90	0,728	25	–	–	5,5	7,5	270	1130 x 490 x 920	180		
CL 7-	13	190	90	0,525	19	–	–	5,5	7,5	270	1130 x 490 x 920	185		
CL 7,5-	10	150	90	–	–	0,68	24	5,5	7,5	270	1130 x 490 x 920	180		
CL 10-	10	150	350	1,060	37	1,03	36	7,5	10,0	500	1734 x 620 x 1229	370		
CL 15-	10	150	350	1,700	60	–	–	11,0	15,0	500	1734 x 620 x 1229	410		
CL 20-	10	150	350	2,240	79	2,17	77	15,0	20,0	500	1734 x 620 x 1229	430		

* Liefermenge der Gesamtanlage nach ISO 1217, Anhang C, bei 20°C Umgebungstemperatur und Höchstdruck. Emissions-Schalldruckpegel nach PN8NTC2.3 ab 59 dB(A).