

BOGE Type	Max. pressure**		Effective free air delivery*		Motor power				Dimensions	Dimensions	Compressed air outlet	Weight silenced kg	Weight super-silenced kg
	bar	psig	m ³ /min	cfm	Main drive motor kW	HP	Fan motor kW	HP	silenced W x D x H (mm)	super-silenced W x D x H (mm)			
SF 60-2	8	115	1.75-7.00	62- 247	45	60	1.1	1.5	1620x 960x1450	1620x 960x1950	G 1 ¹ / ₄	885	915
	10	150	1.58-6.34	56- 224	45	60	1.1	1.5	1620x 960x1450	1620x 960x1950	G 1 ¹ / ₄	885	915
	13	190	1.34-5.36	47- 189	45	60	1.1	1.5	1620x 960x1450	1620x 960x1950	G 1 ¹ / ₄	885	915
SF 100-2	8	115	3.02-12.1	106- 428	75	100	2.2	3.0	2000x1065x1450	2000x1065x1950	G 1 ¹ / ₂	1350	1400
	10	150	2.62-10.5	93- 371	75	100	2.2	3.0	2000x1065x1450	2000x1065x1950	G 1 ¹ / ₂	1350	1400
	13	190	2.30- 9.2	81- 325	75	100	2.2	3.0	2000x1065x1450	2000x1065x1950	G 1 ¹ / ₂	1350	1400
SF 150	8	115	4.60-18.4	163- 650	110	150	4.0	5.5	2365x1335x1750	2365x1335x2250	G 2 ¹ / ₂	2200	2260
	10	150	4.08-16.3	144- 575	110	150	4.0	5.5	2365x1335x1750	2365x1335x2250	G 2 ¹ / ₂	2200	2260
	13	190	3.55-14.2	125- 505	110	150	4.0	5.5	2365x1335x1750	2365x1335x2250	G 2 ¹ / ₂	2200	2260

*Free air delivery for complete package in accordance with ISO 1217, Appendix C, at 20°C ambient temperature and maximum pressure.
Emitted sound level as per PN8NTC2.3 from **71 dB(A)**.