

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure* psig	Effective free air delivery cfm	Motor power		Dimensions W x D x H (inches)	Compressed air outlet ANSI	Weight silenced lbs	Weight super-silenced lbs
			Main drive hp	Fan motor hp				
S 56-4 LF N	100	102-399	75	3	94 x 56 x 79	2.5"	4740	4780
S 56-4 LF N	110	99-384	75	3	94 x 56 x 79	2.5"	4740	4780
S 56-4 LF N	125	84-355	75	3	94 x 56 x 79	2.5"	4740	4780
S 56-4 LF N	150	86-309	75	3	94 x 56 x 79	2.5"	4740	4780
S 76-4 N	100	532	100	3	92 x 56 x 79	2.5"	4770	4810
S 76-4 N	125	456	100	3	92 x 56 x 79	2.5"	4770	4810
S 76-4 N	150	444	100	3	92 x 56 x 79	2.5"	4770	4810
S 76-4 L N	150	421	100	3	92 x 56 x 79	2.5"	4570	4610
S 76-4 LF N	100	102-521	100	3	94 x 56 x 79	2.5"	4740	4780
S 76-4 LF N	110	101-506	100	3	94 x 56 x 79	2.5"	4740	4780
S 76-4 LF N	125	100-475	100	3	94 x 56 x 79	2.5"	4740	4780
S 76-4 LF N	150	97-427	100	3	94 x 56 x 79	2.5"	4740	4780
S 90-4 N	100	626	125	4	92 x 56 x 79	2.5"	4970	5010
S 90-4 N	125	565	125	4	92 x 56 x 79	2.5"	4970	5010
S 90-4 N	150	540	125	4	92 x 56 x 79	2.5"	4970	5010
S 90-4 LF N	100	102-601	125	4	94 x 56 x 79	2.5"	4960	5005
S 90-4 LF N	110	101-587	125	4	94 x 56 x 79	2.5"	4960	5005
S 90-4 LF N	125	100-558	125	4	94 x 56 x 79	2.5"	4960	5005
S 90-4 LF N	150	98-512	125	4	94 x 56 x 79	2.5"	4960	5005
S 110-4 N	100	723	150	4	92 x 56 x 79	2.5"	4990	5030
S 110-4 N	125	647	150	4	92 x 56 x 79	2.5"	4990	5030
S 110-4 N	150	614	150	4	92 x 56 x 79	2.5"	4990	5030
S 110-4 LF N	100	226-700	150	4	94 x 56 x 79	2.5"	4970	5010
S 110-4 LF N	110	204-679	150	4	94 x 56 x 79	2.5"	4970	5010
S 110-4 LF N	125	158-634	150	4	94 x 56 x 79	2.5"	4970	5010
S 110-4 LF N	150	87-564	150	4	94 x 56 x 79	2.5"	4970	5010

* Also available in pressures up to 200 PSI - C/F

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure*	Effective free air delivery	Motor power		Dimensions	Compressed air outlet ANSI	Weight silenced	Weight super-silenced
	psig		cfm	Main drive				
			hp	hp	W x D x H (inches)		lbs	lbs
S 111-4 N	100	733	150	4	116 x 64 x 79	3"	7830	7940
S 111-4 N	125	648	150	4	116 x 64 x 79	3"	7830	7940
S 111-4 N	150	601	150	4	116 x 64 x 79	3"	7830	7940
S 111-4 LF N	100	193-745	150	4	118 x 64 x 79	3"	7830	7940
S 111-4 LF N	110	192-726	150	4	118 x 64 x 79	3"	7830	7940
S 111-4 LF N	125	190-684	150	4	118 x 64 x 79	3"	7830	7940
S 111-4 LF N	150	187-618	150	4	118 x 64 x 79	3"	7830	7940
S 132-4 L N	100	848	175	4	116 x 64 x 79	3"	7830	7940
S 132-4 L N	125	836	175	4	116 x 64 x 79	3"	7830	7940
S 132-4 N	150	709	175	4	116 x 64 x 79	3"	8050	8160
S 132-4 LF N	100	193-867	175	4	118 x 64 x 79	3"	8050	8160
S 132-4 LF N	110	192-846	175	4	118 x 64 x 79	3"	8050	8160
S 132-4 LF N	125	190-801	175	4	118 x 64 x 79	3"	8050	8160
S 132-4 LF N	150	187-732	175	4	118 x 64 x 79	3"	8050	8160
S 160-4 N	100	1034	200	7	116 x 64 x 79	3"	8270	8380
S 160-4 N	125	954	200	7	116 x 64 x 79	3"	8270	8380
S 160-4 L N	150	826	200	7	116 x 64 x 79	3"	7940	8050
S 160-4 LF N	100	193-981	200	7	118 x 64 x 79	3"	8270	8380
S 160-4 LF N	110	192-962	200	7	118 x 64 x 79	3"	8270	8380
S 160-4 LF N	125	190-922	200	7	118 x 64 x 79	3"	8270	8380
S 160-4 LF N	150	186-857	200	7	118 x 64 x 79	3"	8270	8380

* Also available in pressures up to 200 PSI - C/F