

## BOGE EO series

Totally oil-free, ultra compact and whisper-quiet



### TECHNICAL DATA

BOGE type	Maximal pressure		Effective free air delivery*		Rated output		Tank capacity Liter	Sound pressure level** dB(A)	Dimensions W x D x H (mm)	Compressed air outlet	Weight kg
	bar	psig	l/min	cfm	kW	hp					
EO 4	8	115	410	14.5	4	5.5	–	60	670 x 1,000 x 970	G 1/2	220
EO 4	10	145	340	12.0	4	5.5	–	60	670 x 1,000 x 970	G 1/2	220
EO 4 D	8	115	410	14.5	4	5.5	–	60	670 x 1,000 x 1,380	G 1/2	305
EO 4 D	10	145	340	12.0	4	5.5	–	60	670 x 1,000 x 1,380	G 1/2	305
EO 4 R	8	115	410	14.5	4	5.5	270	60	745 x 1,785 x 1,670	G 1/2	338
EO 4 R	10	145	340	12.0	4	5.5	270	60	745 x 1,785 x 1,670	G 1/2	338
EO 4 DR	8	115	410	14.5	4	5.5	270	60	745 x 1,785 x 1,670	G 1/2	375
EO 4 DR	10	145	310	12.0	4	5.5	270	60	745 x 1,785 x 1,670	G 1/2	375
EO 4 TR	8	115	820	29.0	2 x 4	2 x 5.5	350	60	1,000 x 1,825 x 1,725	G 1/2	583
EO 4 TR	10	145	680	24.0	2 x 4	2 x 5.5	350	60	1,000 x 1,825 x 1,725	G 1/2	583
EO 6	8	115	620	21.9	5.5	7.5	–	62	670 x 1,000 x 970	G 1/2	255
EO 6	10	145	490	17.3	5.5	7.5	–	59	670 x 1,000 x 970	G 1/2	255
EO 6 D	8	115	620	21.9	5.5	7.5	–	62	670 x 1,000 x 1,380	G 1/2	341
EO 6 D	10	145	490	17.3	5.5	7.5	–	59	670 x 1,000 x 1,380	G 1/2	341
EO 6 R	8	115	620	21.9	5.5	7.5	270	62	745 x 1,785 x 1,670	G 1/2	373
EO 6 R	10	145	490	17.3	5.5	7.5	270	59	745 x 1,785 x 1,670	G 1/2	373
EO 6 DR	8	115	620	21.9	5.5	7.5	270	62	745 x 1,785 x 1,670	G 1/2	410
EO 6 DR	10	145	490	17.3	5.5	7.5	270	59	745 x 1,785 x 1,670	G 1/2	410
EO 6 TR	8	115	1,240	43.8	2 x 5.5	2 x 7.5	350	62	1,000 x 1,825 x 1,725	G 1/2	653
EO 6 TR	10	145	980	34.6	2 x 5.5	2 x 7.5	350	59	1,000 x 1,825 x 1,725	G 1/2	653

\* Delivery quantity measured on ISO 1217: 2009 annex C \*\* Sound pressure level measured according to DIN EN ISO 2151:2009

## BOGE EO series

Totally oil-free, ultra compact and whisper-quiet



### TECHNICAL DATA

BOGE type	Maximal pressure		Effective free air delivery*		Rated output		Tank capacity Liter	Sound pressure level** dB(A)	Dimensions W x D x H (mm)	Compressed air outlet	Weight kg
	bar	psig	l/min	cfm	kW	hp					
EO 7	8	115	880	31.1	7.5	10	–	64	670 x 1,000 x 970	G 1/2	252
EO 7	10	145	700	24.7	7.5	10	–	59	670 x 1,000 x 970	G 1/2	252
EO 7 D	8	115	880	31.1	7.5	10	–	64	670 x 1,000 x 1,380	G 1/2	343
EO 7 D	10	145	700	24.7	7.5	10	–	59	670 x 1,000 x 1,380	G 1/2	343
EO 7 R	8	115	880	31.1	7.5	10	270	64	745 x 1,785 x 1,670	G 1/2	375
EO 7 R	10	145	700	24.7	7.5	10	270	59	745 x 1,785 x 1,670	G 1/2	375
EO 7 DR	8	115	880	31.1	7.5	10	270	64	780 x 1,756 x 1,670	G 1/2	410
EO 7 DR	10	145	700	24.7	7.5	10	270	59	780 x 1,756 x 1,670	G 1/2	410
EO 7 TR	8	115	2 x 880	2 x 31.1	2 x 7.5	2 x 10	350	64	1,000 x 1,825 x 1,725	G 1/2	657
EO 7 TR	10	145	2 x 700	2 x 24.7	2 x 7.5	2 x 10	350	59	1,000 x 1,825 x 1,725	G 1/2	657
EO 11	8	115	1,240	43.8	11	15	–	62	915 x 1,520 x 1,460	G 1	585
EO 11	10	145	980	34.6	11	15	–	59	915 x 1,520 x 1,460	G 1	585
EO 11 D	8	115	1,240	43.8	11	15	–	62	915 x 1,520 x 1,460	G 1	620
EO 11 D	10	145	980	34.6	11	15	–	59	915 x 1,520 x 1,460	G 1	620
EO 15	8	115	1,760	62.2	15	20	–	70	915 x 1,520 x 1,460	G 1	590
EO 15	10	145	1,400	49.4	15	20	–	66	915 x 1,520 x 1,460	G 1	590
EO 15 D	8	115	1,760	62.2	15	20	–	70	915 x 1,520 x 1,460	G 1	625
EO 15 D	10	145	1,400	49.4	15	20	–	66	915 x 1,520 x 1,460	G 1	625
EO 23	8	115	2,640	93.2	22.5	30	–	71	915 x 1,520 x 1,460	G 1	720
EO 23	10	145	2,100	74.2	22.5	30	–	66	915 x 1,520 x 1,460	G 1	720
EO 30	8	115	3,520	124.3	30	40	–	71	915 x 1,520 x 1,880	G 1	900
EO 30	10	145	2,800	98.9	30	40	–	67	915 x 1,520 x 1,880	G 1	900

\* Delivery quantity measured on ISO 1217: 2009 annex C \*\* Sound pressure level measured according to DIN EN ISO 2151:2009