

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure psig	Effective free air delivery cfm	Motor power		Dimensions W x D x H (inches)	Compressed air outlet ANSI	Weight silenced lbs	Weight super-silenced lbs
			Main drive kW	Fan motor hp				
S 56 -4 LF	100	102 - 399	75	3	94x56x79	2 1/2"	4740	4780
S 56 -4 LF	125	94 - 355	75	3	94x56x79	2 1/2"	4740	4780
S 56 -4 LF	150	86 - 309	75	3	94x56x79	2 1/2"	4740	4780
S 56 -4 LF	190	80 - 255	75	3	94x56x79	2 1/2"	4740	4780
S 76 -4 L	150	421	100	3	92x56x79	2 1/2"	4570	4610
S 76 -4	100	532	100	3	92x56x79	2 1/2"	4770	4810
S 76 -4	125	456	100	3	92x56x79	2 1/2"	4770	4810
S 76 -4	150	444	100	3	92x56x79	2 1/2"	4770	4810
S 76 -4	190	359	100	3	92x56x79	2 1/2"	4770	4810
S 76 -4 LF	100	102 - 521	100	3	94x56x79	2 1/2"	4740	4780
S 76 -4 LF	125	100 - 475	100	3	94x56x79	2 1/2"	4740	4780
S 76 -4 LF	150	97 - 427	100	3	94x56x79	2 1/2"	4740	4780
S 76 -4 LF	190	92 - 368	100	3	94x56x79	2 1/2"	4740	4780

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure psig	Effective free air delivery cfm	Motor power		Dimensions W x D x H (inches)	Compressed air outlet ANSI	Weight silenced lbs	Weight super-silenced lbs
			Main drive kW	Fan motor hp				
S 90 -4	100	626	125	4	92x56x79	2 1/2"	4970	5010
S 90 -4	125	565	125	4	92x56x79	2 1/2"	4970	5010
S 90 -4	150	540	125	4	92x56x79	2 1/2"	4970	5010
S 90 -4	190	457	125	4	92x56x79	2 1/2"	4970	5010
S 90 -4 LF	100	102 - 601	125	4	94x56x79	2 1/2"	4960	5005
S 90 -4 LF	125	100 - 558	125	4	94x56x79	2 1/2"	4960	5005
S 90 -4 LF	150	98 - 512	125	4	94x56x79	2 1/2"	4960	5005
S 90 -4 LF	190	94 - 450	125	4	94x56x79	2 1/2"	4960	5005
S 110 -4	100	723	150	4	92x56x79	2 1/2"	4990	5030
S 110 -4	125	647	150	4	92x56x79	2 1/2"	4990	5030
S 110 -4	150	614	150	4	92x56x79	2 1/2"	4990	5030
S 110 -4	190	541	150	4	92x56x79	2 1/2"	4990	5030
S 110 -4 LF	100	226 - 700	150	4	94x56x79	2 1/2"	4970	5010
S 110 -4 LF	125	158 - 634	150	4	94x56x79	2 1/2"	4970	5010
S 110 -4 LF	150	87 - 564	150	4	94x56x79	2 1/2"	4970	5010
S 110 -4 LF	190	97 - 507	150	4	94x56x79	2 1/2"	4970	5010