

BOGE C-2 Baureihe

Kompakt. Effizient. Leise.



TECHNISCHE DATEN

BOGE Typ	Höchst- druck	Effektive Liefermenge	Nennleistung Antriebsmotor	Maße	Druckluft- austritt	Schalldruckpegel superschall- gedämmt	Gewicht superschall- gedämmt
	bar	m ³ /min	kW	B x T x H (mm)		dB(A)	kg
C 12-2	7,5	1,97	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	10	1,71	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	13	1,31	11	1610 x 915 x 1380	G 1"	63	522
C 12-2 L	7,5	1,82	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 L	10	1,74	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	7,5	0,53 - 2,02	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	10	0,52 - 1,71	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	13	0,51 - 1,31	11	1610 x 915 x 1380	G 1"	63	557
C 15-2	7,5	2,56	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	10	2,25	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	13	1,89	15	1610 x 915 x 1380	G 1"	65	532
C 15-2 L	7,5	2,26	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 L	10	2,22	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	7,5	0,53 - 2,63	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	10	0,52 - 2,25	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	13	0,51 - 1,89	15	1610 x 915 x 1380	G 1"	65	557
C 18-2	7,5	3,12	18,5	1610 x 915 x 1380	G 1"	68	567
C 18-2	10	2,71	18,5	1610 x 915 x 1380	G 1"	68	567
C 18-2	13	2,32	18,5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	7,5	0,54 - 3,19	18,5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	10	0,52 - 2,71	18,5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	13	0,72 - 2,32	18,5	1610 x 915 x 1380	G 1"	68	567
C 22-2	7,5	3,64	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	10	3,21	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	13	2,74	22	1610 x 915 x 1380	G 1"	69	597
C 22-2 LF	7,5	0,54 - 3,73	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	10	0,52 - 3,21	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	13	0,72 - 2,74	22	1610 x 915 x 1380	G 1"	69	602

BOGE C-2 Baureihe

Kompakt. Effizient. Leise.



TECHNISCHE DATEN

BOGE Typ	Mit Trockner (D)		Mit 500 L Behälter (R)		Mit 500 L Behälter und Trockner (DR)	
	Maße	Gewicht super- schallgedämmt	Maße	Gewicht super- schallgedämmt	Maße	Gewicht super- schallgedämmt
	B x T x H (mm)	kg	B x T x H (mm)	kg	B x T x H (mm)	kg
C 12-2 _ C 15-2	1610 x 915 x 1380	562/582	2036 x 915 x 1915	673/683	2036 x 915 x 1915	713/733
C 12-2 L _ C 15-2 L	1610 x 915 x 1380	557/567	2036 x 915 x 1915	668	2036 x 915 x 1915	708/718
C 12-2 LF _ C 15-2 LF	1610 x 915 x 1380	597	2036 x 915 x 1915	708/698	2036 x 915 x 1915	748
C 18-2 _ C 22-2	1610 x 915 x 1380	617/647	2036 x 915 x 1915	718/748	2036 x 915 x 1915	768/798
C 18-2 LF _ C 22-2 LF	1610 x 915 x 1380	617/652	2036 x 915 x 1915	718/753	2036 x 915 x 1915	768/803