

BOGE C-2 series

Compact. Efficient. Quiet.



TECHNICAL DATA

BOGE type	Max. pressure	Effective free air delivery	Motor power	Dimensions	Compressed-air outlet	Sound pressure level super sound insulation	Weight with super sound insulation
	bar	m ³ /min	kW	W x D x H (mm)		dB(A)	kg
C 12-2	7.5	1.97	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	10	1.71	11	1610 x 915 x 1380	G 1"	63	522
C 12-2	13	1.31	11	1610 x 915 x 1380	G 1"	63	522
C 12-2 L	7.5	1.82	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 L	10	1.74	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	7.5	0.53 - 2.02	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	10	0.52 - 1.71	11	1610 x 915 x 1380	G 1"	63	557
C 12-2 LF	13	0.51 - 1.31	11	1610 x 915 x 1380	G 1"	63	557
C 15-2	7.5	2.56	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	10	2.25	15	1610 x 915 x 1380	G 1"	65	532
C 15-2	13	1.89	15	1610 x 915 x 1380	G 1"	65	532
C 15-2 L	7.5	2.26	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 L	10	2.22	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	7.5	0.53 - 2.63	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	10	0.52 - 2.25	15	1610 x 915 x 1380	G 1"	65	557
C 15-2 LF	13	0.51 - 1.89	15	1610 x 915 x 1380	G 1"	65	557
C 18-2	7.5	3.12	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2	10	2.71	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2	13	2.32	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	7.5	0.54 - 3.19	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	10	0.52 - 2.71	18.5	1610 x 915 x 1380	G 1"	68	567
C 18-2 LF	13	0.72 - 2.32	18.5	1610 x 915 x 1380	G 1"	68	567
C 22-2	7.5	3.64	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	10	3.21	22	1610 x 915 x 1380	G 1"	69	597
C 22-2	13	2.74	22	1610 x 915 x 1380	G 1"	69	597
C 22-2 LF	7.5	0.54 - 3.73	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	10	0.52 - 3.21	22	1610 x 915 x 1380	G 1"	69	602
C 22-2 LF	13	0.72 - 2.74	22	1610 x 915 x 1380	G 1"	69	602

BOGE C-2 series

Compact. Efficient. Quiet.



TECHNICAL DATA

BOGE type	With dryer (D)		With 500 l receiver (R)		With 500 l receiver and dryer (DR)	
	Dimensions	Weight super sound insulation	Dimensions	Weight super sound insulation	Dimensions	Weight super sound insulation
	W x D x H (mm)	kg	W x D x H (mm)	kg	W x D x H (mm)	kg
C 12-2 _ C 15-2	1610 x 915 x 1380	562/582	2036 x 915 x 1915	673/683	2036 x 915 x 1915	713/733
C 12-2 L _ C 15-2 L	1610 x 915 x 1380	557/567	2036 x 915 x 1915	668	2036 x 915 x 1915	708/718
C 12-2 LF _ C 15-2 LF	1610 x 915 x 1380	597	2036 x 915 x 1915	708/698	2036 x 915 x 1915	748
C 18-2 _ C 22-2	1610 x 915 x 1380	617/647	2036 x 915 x 1915	718/748	2036 x 915 x 1915	768/798
C 18-2 LF _ C 22-2 LF	1610 x 915 x 1380	617/652	2036 x 915 x 1915	718/753	2036 x 915 x 1915	768/803