

BOGE EO N series

Totally oil-free, ultra compact and whisper-quiet



TECHNICAL DATA

BOGE type	Maximal pressure		Effective free air delivery*		Rated output		Tank capacity	Sound pressure level**	Dimensions	Compressed air outlet	Weight
	bar	psig	l/min	cfm	kW	hp	Liter	dB(A)	W x D x H (inch)	inch	pounds
EO 4 N	8	115	410	14.5	4	5.5	-	60	26.4 x 39.4 x 38.2	1/2 NPT	485
EO 4 N	10	145	340	12.0	4	5.5	-	60	26.4 x 39.4 x 38.2	1/2 NPT	485
EO 6 N	8	115	620	21.9	5.5	7.5	-	62	26.4 x 39.4 x 38.2	1/2 NPT	562
EO 6 N	10	145	490	17.3	5.5	7.5	-	59	26.4 x 39.4 x 38.2	1/2 NPT	562
EO 7 N	8	115	880	31.1	7.5	10	-	64	26.4 x 39.4 x 38.2	1/2 NPT	556
EO 7 N	10	145	700	24.7	7.5	10	-	59	26.4 x 39.4 x 38.2	1/2 NPT	556
EO 11 N	8	115	1,240	43.8	11	15	-	62	36.0 x 59.8 x 57.5	1 NPT	1,290
EO 11 N	10	145	980	34.6	11	15	-	59	36.0 x 59.8 x 57.5	1 NPT	1,290
EO 15 N	8	115	1,760	62.2	15	20	-	70	36.0 x 59.8 x 57.5	1 NPT	1,300
EO 15 N	10	145	1,400	49.4	15	20	-	66	36.0 x 59.8 x 57.5	1 NPT	1,300
EO 23 N	8	115	2,640	93.2	22.5	30	-	71	36.0 x 59.8 x 57.5	1 NPT	1,587
EO 23 N	10	145	2,100	74.2	22.5	30	-	66	36.0 x 59.8 x 57.5	1 NPT	1,587
EO 30 N	8	115	3,520	124.3	30	40	-	71	36.0 x 59.8 x 74.0	1 NPT	1,984
EO 30 N	10	145	2,800	98.9	30	40	-	67	36.0 x 59.8 x 74.0	1 NPT	1,984

* Delivery quantity measured on ISO 1217: 2009 annex C ** Sound pressure level measured according to DIN EN ISO 2151:2009