



TECHNISCHE DATEN

BOGE Typ	Höchstdruck bar	Effektive Liefermenge* (50 Hz)		Nennleistung Hauptantrieb kW	Lüftermotor kW	Maße schallgedämmt B x T x H (mm)	Gewicht schallgedämmt kg
		min m³/min	max m³/min				
SO 110-3	7,5	–	19,80	110	0,75	3086 x 1820 x 2010	3800
	8	–	17,60	110	0,75	3086 x 1820 x 2010	3800
	10	–	15,50	110	0,75	3086 x 1820 x 2010	3800
SO 132-3	7,5	–	24,60	132	0,75	3086 x 1820 x 2010	3950
	8	–	21,30	132	0,75	3086 x 1820 x 2010	3950
	10	–	19,70	132	0,75	3086 x 1820 x 2010	3950
SO 160-3	7,5	–	29,10	160	0,75	3086 x 1820 x 2010	4030
	8	–	26,30	160	0,75	3086 x 1820 x 2010	4030
	10	–	24,50	160	0,75	3086 x 1820 x 2010	4030
SO 110-3 F	7,5	9,33	20,34	110	0,75	3086 x 1820 x 2010	4120
	8	9,23	19,61	110	0,75	3086 x 1820 x 2010	4120
	10	8,06	17,00	110	0,75	3086 x 1820 x 2010	4120
SO 132-3 F	7,5	10,72	23,84	132	0,75	3086 x 1820 x 2010	4270
	8	9,23	21,71	132	0,75	3086 x 1820 x 2010	4270
	10	8,06	19,27	132	0,75	3086 x 1820 x 2010	4270
SO 160-3 F	7,5	12,83	29,02	160	0,75	3086 x 1820 x 2010	4350
	8	11,50	26,40	160	0,75	3086 x 1820 x 2010	4350
	10	10,58	24,47	160	0,75	3086 x 1820 x 2010	4350

* Liefermengen gemessen nach ISO 1217:2009 Anhang C.