

BOGE T series

The efficient turbo for oil-free compressed air



TECHNICAL DATA

BOGE Typ	Pressure bar	Effective free air delivery (50 Hz and 60 Hz)		Rated output			Noise level dB (A)	Dimensions W x D x H		Weight kg
				Main drive kW	Fan motor*			mm		
					m ³ /min	cfm			m ³ /min	
T 220	5.0	20.30	38.40	220	0	0	70	1545 x 2340 x 1930	1900	
T 220	6.0	21.50	37.50	220	0	0	70	1545 x 2340 x 1930	1900	
T 220	7.0	23.50	36.20	220	0	0	70	1545 x 2340 x 1930	1900	
T 220	7.5	24.80	35.60	220	0	0	70	1545 x 2340 x 1930	1900	
T 220	8.0	26.00	34.50	220	0	0	70	1545 x 2340 x 1930	1900	

*Fan motor is not required.

BOGE T series

The efficient turbo for oil-free compressed air



TECHNICAL DATA

BOGE Typ	Pressure bar	Effective free air delivery (50 Hz and 60 Hz)		Rated output				Noise level dB (A)	Dimensions W x D x H		Weight kg
				Main drive		Fan motor*			mm		
				m ³ /min	cfm	kW	m ³ /min		cfm		
LPT 150	2.0	17.74	43.28	150	0	0	73	1330 x 1970 x 1930	1320		
LPT 150	2.5	20.46	40.74	150	0	0	73	1330 x 1970 x 1930	1320		
LPT 150	3.0	23.17	37.79	150	0	0	73	1330 x 1970 x 1930	1320		
LPT 150	3.5	25.89	34.55	150	0	0	73	1330 x 1970 x 1930	1320		
LPT 150	4.0	28.60	31.10	150	0	0	73	1330 x 1970 x 1930	1320		

*Fan motor is not required.