

BOGE S-4 Baureihe

Designed to take the lead



TECHNISCHE DATEN

BOGE Typ	Höchst- druck bar	Effektive Liefermenge m³/min	Nennleistung		Maße B x T x H (mm)	Druckluft- austritt	Gewicht schall- gedämmt kg	Gewicht superschall- gedämmt kg
			Haupt- antrieb kW	Lüfter- motor kW				
S 38-4 LF(D)	7,5	1,32–7,01	37	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.345 (1.555)	1.365 (1.575)
S 38-4 LF(D)	10	1,74–6,01	37	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.345 (1.555)	1.365 (1.575)
S 38-4 LF(D)	13	1,90–4,60	37	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.345 (1.555)	1.365 (1.575)
S 45-4 LF(D)	7,5	1,26–8,39	45	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.365 (1.575)	1.385 (1.595)
S 45-4 LF(D)	10	1,72–7,33	45	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.365 (1.575)	1.385 (1.595)
S 45-4 LF(D)	13	1,91–6,04	45	2,2	2.080 (2.550) x 1.200 x 1.720	G 1 1/2	1.365 (1.575)	1.385 (1.595)
S 55-4 LF(D)	7,5	2,37–10,69	55	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)
S 55-4 LF(D)	10	2,44–8,70	55	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)
S 55-4 LF(D)	13	3,33–7,40	55	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)
S 55-4 L(D)	7,5	10,01	55	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	2.030 (2.210)	2.070 (2.250)
S 75-4 LF(D)	7,5	2,37–13,54	75	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)
S 75-4 LF(D)	10	2,84–11,71	75	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)
S 75-4 LF(D)	13	3,33–9,50	75	2,2	2.100 (2.570) x 1.200 x 1.720	DN 65	1.770 (1.950)	1.810 (1.990)