

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

BOGE type	Max. pressure	Effective free air delivery	Rated output		Dimensions W x D x H (mm)	Compressed-air outlet	Weight with sound insulation kg	Weight with super sound insulation kg
	bar	m ³ /min	Main-drive kW	Fan-motor kW				
S 38-4 LF(D)	7.5	1.32–7.01	37	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,345 (1,555)	1,365 (1,575)
S 38-4 LF(D)	10	1.74–6.01	37	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,345 (1,555)	1,365 (1,575)
S 38-4 LF(D)	13	1.90–4.60	37	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,345 (1,555)	1,365 (1,575)
S 45-4 LF(D)	7.5	1.26–8.39	45	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,365 (1,575)	1,385 (1,595)
S 45-4 LF(D)	10	1.72–7.33	45	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,365 (1,575)	1,385 (1,595)
S 45-4 LF(D)	13	1.91–6.04	45	2.2	2,080 (2,550) x 1,200 x 1,720	G 1 1/2	1,365 (1,575)	1,385 (1,595)
S 55-4 LF(D)	7.5	2.37–10.69	55	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)
S 55-4 LF(D)	10	2.44–8.70	55	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)
S 55-4 LF(D)	13	3.33–7.40	55	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)
S 55-4 L(D)	7.5	10.01	55	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	2,030 (2,210)	2,070 (2,250)
S 75-4 LF(D)	7.5	2.37–13.54	75	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)
S 75-4 LF(D)	10	2.84–11.71	75	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)
S 75-4 LF(D)	13	3.33–9.50	75	2.2	2,100 (2,570) x 1,200 x 1,720	DN 65	1,770 (1,950)	1,810 (1,990)