

La nouvelle **BOGE S-4** série



CARACTÉRISTIQUES TECHNIQUES

| BOGE Type | Pression maximale | Débit reel | Puissance nominale | | Dimensions | Sortie d'air comprimé | Poids insonorisé | Poids superinsonorisé |
|-------------|-------------------|------------|--------------------|-----------------------|--------------------|-----------------------|------------------|-----------------------|
| | | | Moteur principal | Moteur de ventilateur | | | | |
| | bar | m³/min | kW | kW | L x P x H (mm) | | kg | kg |
| S 111-4 | 7.5 | 20.2 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 | 10 | 17.1 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 | 13 | 14.4 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 7.5 | 5.5 - 20.6 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 10 | 5.3 - 17.8 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 13 | 4.9 - 14.4 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 L | 7.5 | 19.9 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3450 | 3500 |
| S 111-4 D | 7.5 | 20.2 | 110 | 3.0 | 3490 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 111-4 D | 10 | 17.1 | 110 | 3.0 | 3490 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 111-4 D | 13 | 14.4 | 110 | 3.0 | 3490 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 111-4 LFD | 7.5 | 5.5 - 20.6 | 110 | 3.0 | 3540 x 1620 x 1990 | DN 80 | 3800 | 3850 |
| S 111-4 LFD | 10 | 5.3 - 17.8 | 110 | 3.0 | 3540 x 1620 x 1990 | DN 80 | 3800 | 3850 |
| S 111-4 LFD | 13 | 4.9 - 14.4 | 110 | 3.0 | 3540 x 1620 x 1990 | DN 80 | 3800 | 3850 |
| S 111-4 LD | 7.5 | 19.9 | 110 | 3.0 | 3490 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 | 7.5 | 23.2 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 | 10 | 21.1 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 | 13 | 17.2 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 7.5 | 5.5 - 24.0 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 10 | 5.3 - 21.0 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 13 | 5.0 - 17.9 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 L | 10 | 19.3 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 160-4 | 7.5 | 27.6 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 | 10 | 25.0 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 | 13 | 21.2 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 LF | 7.5 | 5.5 - 27.3 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 LF | 10 | 5.3 - 24.6 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 LF | 13 | 5.0 - 21.2 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 L | 13 | 19.3 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3600 | 3650 |